



1937L 19" LCD Open-Frame Touchmonitor

High-quality panel and choice of touch technology in a compact form factor

The 1937L open-frame touchmonitor delivers a cost-effective touch solution for OEMs and systems integrators, and complements the expanded family of Elo touch solutions for gaming and amusement, retail self-service and kiosk applications. This compact touchmonitor is "designed for touch," with proven expertise and reliability built-in, not added as an afterthought by altering an existing monitor.

Like all Elo open-frame touchmonitors, the specifications and tooling are controlled to ensure a long product life, which is important in maintaining continuity for all phases of project rollouts and servicing. The 1937L features an injection-molded bezel with a virtually invisible watertight seal, thus making it a good choice to withstand the rigors of public use. Narrow borders, black anodized bezel hardware, multiple mounting options, and dual serial/USB touch interface (APR is USB only) add to the touchmonitor's flexibility. Worldwide agency approvals cover the entire monitor that is developed, built and supported by Elo Touch Solutions, a true single-source supplier.

The 1937L is available with a choice of one of Elo's industry-leading touch technologies: Acoustic Pulse Recognition (APR), AccuTouch 5-wire resistive or IntelliTouch surface acoustic wave. The comprehensive range of features includes an analog

interface, multi-lingual on-screen display (OSD), mounting VESA standard, mounting brackets, cabled remote on-screen display (OSD), and worldwide compliance.

Features

- High quality panel with 160° x 160° viewing angle
- 800:1 contrast ratio
- Long-lasting product cycle—enclosure controlled by Elo specifications
- Future generation panels phased-in without external changes
- Integrated precision mini-bezel with watertight 0.5 mm seal
- Mounting options including rear-mount (with two included mounting brackets) and VESA mount
- Acoustic Pulse Recognition (APR) touch technology with USB interface; AccuTouch 5-wire resistive and IntelliTouch touch technologies with dual serial/USB touch interfaces
- Integrated multilingual on-screen display (OSD), connector for optional remote on-screen display (OSD)
- Worldwide agency approvals
- 3 year warranty
- 3D electronic design files available

1937L 19" LCD Open-Frame Touchmonitor Specifications

Case/Bezel color	Steel/black
Display	Size: 19.0" diagonal; Type: Active matrix TFT LCD; Aspect ratio: 5 x 4
Useful screen area	Horizontal: 14.8" (376mm); Vertical 11.9" (301mm)
Monitor dimensions	Width: 16.3" (415mm); Height: 13.5" (343mm); Depth: 2.0" (51mm)
Optimal (native) resolution	1280 x 1024
Other supported resolutions	512 x 247 @ 60Hz; 512 x 248 @ 60Hz; 640 x 350 @ 70Hz; 640 x 480 @ 60, 61, 66, 72, 75 Hz 720 x 400 @ 70Hz; 800 x 600 @ 56, 60, 72, 75Hz; 832 x 624 @ 75Hz; 1024 x 768 @ 60, 65, 70, 75Hz; 1152 x 864 @ 75Hz; 1280 x 1024 @ 60, 75Hz
Colors	16.7 million colors
Brightness (typical)	LCD panel: 250 nits; with AccuTouch: 200 nits; with Acoustic Pulse Recognition: 225 nits; with IntelliTouch: 225 nits
Response time (typical)	10 msec
Viewing angle (typical)	Horizontal: 160° total; Vertical: 155° total
Contrast ratio (typical)	800:1
Input video format	Analog VGA
Input video signal connector	Mini D-Sub 15-Pin VGA type
Input frequency	Horizontal: 31.5-80.0 kHz; Vertical: 56.3-75 Hz
Power supply	External DC—optional power brick (sold separately) Input voltage—DC: +12VDC ±5% Input power connector specification (monitor)—Type: DC Barrel Jack; Barrel inner diameter: 6.4mm (±0.3mm); Pin outer diameter: 2.0mm (+0.0 -0.1mm); Barrel depth: 8.8mm (±0.3mm) Power connector (power brick)—Type: DC Barrel Plug; Barrel outer diameter: 5.5mm (±0.1mm); Pin inner diameter: 2.1mm (±0.1mm); Barrel length: 9.5mm (±0.5mm)
Power consumption (typical)	Monitor: 38W; Monitor and power brick: 43W
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 60°C (-4°F to 140°F)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Weight	Actual: 5.2kg (11.5 lbs); Shipping: 7.3kg (16.1 lbs)
Shipping box dimensions (W x D x H)	20.28" (515mm) x 17.72" (450mm) x 6.89" (175mm)
Warranty	Touchmonitor: 3 years
Mean time between failures (MTBF)	50,000 hours demonstrated
Agency approvals	UL, cUL (Recognized) , TUV Bauart Mark, Argentina S, CE, FCC, VCCI, IC, C-TICK (Class B), NOM, BSMI, KCC, CCC, China RoHS
On-screen display (OSD)	Controls (optional remote with 1.8m cable): Auto/Sel, up, down, menu Controls (back): menu, left, right, select, power Settings: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall Languages: English, German, Spanish, Japanese, French Lockouts: power, user controls
Mounting options	75mm or 100mm VESA mount; Rear mount or with included standard mounting brackets; Front mount with optional bezel; Rack mount with optional bracket
Sealing	Touchscreen sealed to bezel; Touchscreen sealed to LCD

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America	800-ELO-TOUCH	Europe	Asia-Pacific	Latin America
Elo Touch Solutions	Tel 1-650-361-4800	Tel +32 (0)16 35 21 00	Tel +81 (45) 478-2161	Tel 786-923-0251
301 Constitution Drive	Fax 1-650-361-4722	Fax +32 (0)16 35 21 01	Fax +81 (45) 478-2180	Fax 305-931-0124
Menlo Park, CA 94025-1110	customerservice@elotouch.com	elosales@elotouch.com	www.tps.co.jp	www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and IntelliTouch are trademarks of Elo Touch Solutions, Inc.
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 10/12