



3200L 32" Interactive Digital Signage (IDS) Touch Display

The Elo Touch Solutions 32-inch 3200L is a large-format canvas for commercial interactive media applications bringing interactivity to digital signage. By combining precision touchscreen technology with a professional-grade, large format LCD panel, the 3200L is rugged enough to last in high traffic, public access environments. With the easy, two-step installation of one of the optional computer modules, the 3200L is a true high-performance touch solution for digital displays.

Features and Benefits:

- A choice of two pure-glass touchscreen technologies for visual clarity:
 - the reliable, durable IntelliTouch Plus for a responsive multi-touch experience
 - the seamless, zero-bezel Acoustic Pulse Recognition (APR) for an elegant appearance and touch recognition by finger, prosthetic, stylus, card, or pen
- Built with a durable steel chassis to withstand the rigors of public use over consumer-type displays
- Field-installable, high-performance computer modules in three processing models:
 - ECM1 with the Intel Celeron Dual-Core 2.2GHz
 - ECM2 with the Intel Core 2 Duo 3.0GHz
 - ECM3 with the Intel Core i5 2.5GHz
- Lock-out power and display controls to minimize tampering
 - Built-in speakers expand audio capabilities
 - Mountable in landscape or portrait orientation to suit a variety of design layouts
 - Measure real-time advertising and content effectiveness with interactive feedback



3200L 32" Interactive Digital Signage (IDS) Touch Display

Model	3200L
Useful screen area	Horizontal: 27.5" (698 mm); Vertical: 15.4" (392 mm)
Monitor dimensions (without stand)	Width: 31.4" (797 mm); Depth: 5.4" (136 mm); Height: 19.2" (487 mm)
Touch technology	Zero-bezel Acoustic Pulse Recognition (APR), IntelliTouch Plus
Speakers	A pair of 10 W stereo speakers facing down (in landscape mode)
Audio input connector	3.5 mm TRS jack
Audio input signal range	1 Vrms max stereo signal (standard PC line out)
Headphone output connector	3.5 mm TRS jack
Headphone output signal (for 1KHz signal)	Delivers 90 mW of power into a 32 ohm stereo load
LCD technology	Active matrix TFT LCD
Diagonal size	31.5"
Aspect ratio	16:9
On-screen display (OSD)	Controls: menu, up, down, select; settings: brightness, contrast, clock, phase, auto-adjust, H-position, V-position; maintain aspect ratio, sharpness, color temperature, OSD timeout, OSD language, mounting, OSD H-position, OSD V-position, volume, mute, recall defaults, video source, audio source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, power; accessible through switches on the rear, or through the standard Elo OSD control box.
Stand options	Optional stand available, order Part Number E953908
Mounting options	VESA MIS-F, 400 x 200, Y, 6, 90
Native (optimal) resolution	1366 x 768 at 60 Hz
Other supported resolutions	640 x 480 at 60 Hz; 720 x 480 at 60 Hz; 800 x 600 at 56, 60 Hz; 1024 x 768 at 60 Hz; 1280 x 720 at 50, 60 Hz; 1280 x 960 at 60 Hz; 1280 x 1024 at 60 Hz; 1366 x 768 at 60 Hz; 1440 x 900 at 60 Hz; 1680 x 1050 at 60 Hz; 1920 x 1080 at 50, 60 Hz
Colors	16.7 million
Brightness (typical)	LCD panel: 450 nits; with APR: 405 nits; IntelliTouch Plus: 405
Response time (Tr + Tf) total (typical)	20 msec
Viewing angle (typical)	Horizontal: ±89° or 178° total; Vertical: ±89° or 178° total
Contrast ratio (typical)	3500:1
Input video format	Analog VGA, HDMI 1.3
Input video signal connector	Female DE-15 for Analog VGA; HDMI Type A receptacle for HDMI
Input frequency	Horizontal: 32-80 kHz; Vertical: 50-61 Hz
Power supply	Internal AC
Input voltage	100-240 VAC, 50/60 Hz
Power connector	IEC 60320 C14
Power consumption (typical)	Monitor only: ON, max. audio, 100 V/60 Hz: 111 W; SLEEP, 100 V/60 Hz: 12 W; OFF, 100 V/60 Hz: 11.5 W
Temperature	Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 50°C (-4°F to 122°F)
Humidity (non-condensing)	Operating: 20-80%; Storage: 10-90%
Weight	Actual: w/o Computer Module 46.3 lb (21.0 Kg); with Computer Module 52.0 lb (23.6 Kg) Shipping: 68.3 lb (31.0 Kg)
Shipping	TBD (Computer Module shipped separately)
Shipping box dimensions	37.0" (939 mm) x 11.0" (280 mm) x 25.0" (635 mm)
Warranty	3 years
MTBF	50,000 hours demonstrated
Agency approvals	S-mark, C-Tick, cUL, CCC, NOM, GOST, UL; Elo declarations: CE, IC, VCC, FCC

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
301 Constitution Drive
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4800

Fax 1-650-361-4722

customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00

Fax +32 (0)16 35 21 01

elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161

Fax +81 (45) 478-2180

www.tps.co.jp

Latin America

Tel 786-923-0251

Fax 305-931-0124

www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo), Elo Touch Solutions and IntelliTouch are trademarks of Elo Touch Solutions, Inc.
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. 10/12